

**Application No.:** 10/582,417  
**Filing Date:** May 23, 2007

**APPENDIX A:**  
**Substitute Specification**

**SYSTEM AND ARRANGEMENT FOR PRODUCTION AND INSERTION OF A  
DENTAL BRIDGE STRUCTURE**

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is the U.S. National Phase under 35 U.S.C. § 371 of International Application No. PCT/SE04/01527, filed October 22, 2004, which claims priority under 35 U.S.C. § 119 to Swedish Patent Application No. SE 0303309, filed December 10, 2003.

BACKGROUND OF THE INVENTION

[0002] The following disclosure present invention relates inter alia to a system for production and insertion of a real dental bridge structure in a real jaw bone structure by means of a number of successive ~~function-steps effected-performed by using~~ equipment belonging to one ~~two~~ or more ~~different~~ parties.

SUMMARY

[0003] In certain embodiments, The equipment comprises identification equipment, a computer appliance, stereolithography equipment, equipment for production of a physical template, equipment for production of a working model in cooperation with an articulator, equipment for production of the dental bridge structure and insertion equipment for fitting the dental bridge structure on the implant in the jaw bone structure. Jaw bone structure can ~~here~~ relate, for example, to the structure of the upper jaw or lower jaw. The ~~invention-disclosure~~ also relates to ~~an-arrangement-of-~~ a template produced by stereolithography and ~~by-means of~~ information from the computer appliance and used for producing, on the one hand, a dental bridge structure that can be applied on an implant in the jaw bone structure, and, on the other hand, for guiding of hole-forming means, for example a drill, for forming holes for the implants. Generally similar ~~Ssystems of the type in question are already known, and reference may be made inter alia to the~~ may be found in patent application no. SE 0004884-3 filed by the same Applicant.

[0004] ~~It is also already known to use templates on the one hand for forming holes in the jaw bone structure and on the other hand for producing dental bridges. Reference may be made to the procedures used hitherto in the dental field and to the arrangements which in~~

principle are based on quite considerable manual skill. Previous templates are described in Reference may be made to patent application nos. SE 0004885-0, SE 0004886-8, SE 0104431-2, SE 0104432-0, SE 0203898-2, SE 0203899-0 and SE 0203900-6.

[0005] There is a distinct need for improvements to the procedures and arrangements/auxiliaries which have been used hitherto, for example from the point of view of reducing the time and cost associated with making and/or using dental templates. Thus, for example, the production of the template should may be able to be reduced by 30-50% and, inter alia among other advantages, the time of use in the stereolithography machine should be able to be reduced. Despite the reduction from the point of view of time and cost, the precision of the produced products/dental bridges must remain high, as must the securing function, which must be maintained with tolerances of ca. 0.1-0.2 mm. The system and the arrangement must also be non-critical from the handling point of view so that excellent production and insertion results are achieved. In addition, certain time-consuming and cost-intensive operations must be eliminated, and, for example, the source of error in replacing a prosthesis or working model in the correct relation to the jaw bone is to be eliminated. Embodiments described herein allow for relatively high precision while reducing the time and cost associated with production.

[0006] The invention aims to solve these problems inter alia.

[0007] In accordance with the invention disclosure, the remaining operations too must be characterized by well-proven and non-critical techniques which can be dealt with and some or all of the production steps or functions may be performed by parties already operating on the market. The parties must may be able to cooperate in an optimal manner from the technical and financial aspect, with one another. The number of parties must may be able to vary and the functions must be able to production steps may be divided into testing, insertion and handling technique, production by means of STL (stereolithography technology) and model production, and production by the dental technician. For support and possible production of one or more of the functions, higher order other parties may be used involved. Such parties may include parties who provide a generally fully automatic production system for dental products, such as for example of the PROCERA.RTM. type.

[0008] The invention aims to solve this problem too.

[0009] ~~That which can principally be regarded as characterizing a~~ system according to ~~the invention embodiments of the disclosure is inter alia that the~~ a computer appliance is designed to receive, and to present on screen, first information transmitted from ~~the~~ identification equipment and based on detection of ~~the a~~ jaw bone structure. The computer appliance ~~is can be~~ arranged with operating elements ~~by means of which may be used to it is possible to visually enter~~ modification information concerning, on the one hand, a visual dental bridge structure applied on the visual jaw bone structure with associated teeth and dentine. ~~The computer appliance may, and, on the other hand,~~ further be used to modify orientations of the implants in the visual dental bridge structure and visual jaw bone structure. Moreover, the computer appliance is arranged to ~~produce~~ generate or to cause generation of a CAD file based on the first information and the modification information and to transmit the CAD file to the stereolithography machine. ~~The latter must be arranged to issue~~ Second information which can be processed ~~in using~~ the equipment for production of ~~the a~~ physical template with associated ~~which includes~~ through-bores for sleeves arranged to determine the recessed positions and longitudinal directions for ~~the one or more~~ implants. The physical template ~~will can~~ on the one hand form the basis for production of ~~the a~~ working model and, on the other hand, serve as template ~~in a hole formation for forming holes in the jawbone~~ defined with the sleeves ~~and situated in the real jaw bone structure by means of the using~~ insertion equipment (e.g., drill).

[0010] In some embodiment, ~~The~~ identification and computer appliances can be assigned to a first party consisting of a party treating a patient, such as, for example a surgeon or dentist. The stereolithography machine can be assigned to a second party. The equipment for production of the template, working model and real dental bridge structure can be assigned to a third party, for example a dental technician. A fourth party with equipment of a higher order can also be involved. ~~The, which~~ fourth party can ensure, for example, ~~information the provision of information and/or handling or production of one or more of said functions or parts thereof. In certain embodiments, The~~ stereolithography machine can be accessed by any of said parties. ~~Further embodiments of the system according to the invention are set out in the attached dependent claims concerning the system.~~

[0011] An arrangement according to the invention disclosure ~~can be considered to be characterized by the fact that the~~includes a template and the dental bridge structure are provided with through-holes, ~~and the through-holes are provided with sleeves. The sleeves can define, for example, by means of which the degrees of to which the implants are recessed~~ing of the implants and their orientations in the implants can be determined.

[0012] In further ~~developments of the inventive concept~~embodiments, the sleeves are designed ~~with special features for being able to achieve the relevant a degree or amount of~~ recessing in the template. In one embodiment, the sleeves can be anchored to the template with dental cement. In a preferred embodiment, the template is arranged to reproduce or comprise a material or part which corresponds to the dentine or gum replacement over those parts which extend over the portions of jaw bone, in which the ~~the~~ dental bridge is intended to extend over. ~~In some embodiments, the~~ template is produced in said machine from plastic material with a very low coefficient of shrinkage. Further illustrative embodiments are set out in the attached dependent claims concerning the novel arrangement.

[0013] ~~By means of what has been proposed above, a~~In some embodiments, after fixture planning, ~~the planning files can be converted to CAD files and SLA models (rapid prototyping) can be ordered in so-called STL technology. Part of the model can simulate the patient's upper jaw or lower jaw, while another part simulates the patient's dental prosthesis. Thereafter, the working model is produced at the dental laboratory. The template can be planned on a computer using CAD and contains includes all data or information, which means that can be used to order a template can be ordered with the aid of produced by STL technology. When the template is produced in physical form, it can be provided include~~ with sleeves for guiding the drill, implant and anchoring pins. The sleeves can be cemented in place with dental cement.

[0014] Thereafter, ~~the~~ The template can be used as an impression for ~~production producing of the~~ working model (e.g., in plaster), which can is be mounted in an articulator (e.g., with the aid of a bite index against the dental model of the opposite jaw/jaw bone). The dental bridge can be produced on the working model ~~obtained~~. The template can also forms the gum replacement over the implant in the jaw bone and around the ~~spacers in connection with production of the working model.~~

[0015] A ~~presently proposed~~ embodiments of a systems and methods an arrangement according to the invention ~~embodiments~~ of the disclosure will be described below with reference to the attached drawings, ~~in which~~

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0016] FIG. 1 shows, in block diagram form, ~~the example~~ equipment and parties involved according to embodiments described herein.[[,]]

[0017] FIG. 2 shows upper and lower jaws of a patient, a bridge and a template according to embodiments described hereinFIG. 2 shows, in side views and horizontal views, and enlarged in relation to FIG. 1, parts of the function chain according to FIG. 1. [[,]]

[0018] FIG. 3 shows, in vertical cross-section, two different embodiments of sleeves used in the template according to embodiments described herein.[[,]]

[0019] FIG. 4 shows, in vertical cross-section, application of a sleeve in relation to an implant, and a fastening screw for the sleeve and the implant according to embodiments described herein.[[,]]

[0020] FIG. 5 shows, from underneath, a model of an upper jaw in which implants are applied with associated anchoring tubes and anchoring pins which extend horizontally in the dentine between the implants according to embodiments described herein.[[,]]

[0021] FIG. 6 shows a top view of the model according to FIG. 5. [[,]] and

[0022] FIG. 7 shows a perspective view, from the side, ~~of orientations for~~ of implants and anchoring pins in an upper jaw according to embodiments described herein.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0023] A template can be ~~built up~~ planned on using a computer using (e.g., using a CAD tool) by modifying the scanned patient prosthesis. In this way, it is possible to avoid the problem of having to produce the template at a dental laboratory, ~~and t~~ This is an advantage since the template there is made of acrylic or of a plastic which has a certain shrinkage tendency, with deterioration of the precision as a consequence. According to the ~~invention~~ disclosure, the template can be mounted in the articulator with the aid of a bite index. In this way, it is possible to ~~solve the problem of~~ record ing the bite relationships of the jaws. The template is used by the surgeon ~~and solves the problem of~~ to placing the implant at the a planned site in the patient's mouth. ~~The template has an arrangement for its~~

~~anchoring with a~~ Anchoring pins which are inserted from the side of the template between the planned implants may be included. In this way, the template is held in place in the mouth with the aid of a bite index which is produced by the dental technician in the articulator. This solves the problem of obtaining the correct bite relationship between the dental bridge and the opposite jaw after the operation. The template ~~contains all~~ includes data for planning, so that it is generally not necessary to produce the bone part of the patient's jaw. This reduces the production time and costs associated with using ~~in~~ the stereolithography machine. The ~~source of e~~ Error in the form of having to place placing the prosthesis model in the correct relationship to the bone part is ~~eliminated~~ reduced.

[0024] In FIG. 1, a first party is indicated symbolically by 1, a second party by 2, and a third party by 3. The first party can be a surgeon, dentist, etc., who is to test and fit a dental bridge on a patient 4. The second party can be an owner of a stereolithography machine. The third party can be a dental technician. FIG. 1 also indicates a fourth party represented by a ~~fully~~ generally automatic production system for dental products; in the illustrative embodiment the party 5 is designated as PROCERA.RTM. The first party ~~has~~ may have access to identification equipment 6. In addition, the first party has access to a computer appliance 7. The stereolithography machine is symbolized by 8. The dental technician has access to equipment for production of a physical template 9, and equipment 10 for production of a working model in cooperation with an articulator function. In addition, the dental technician produces the final dental bridge ~~in using~~ equipment 11.

[0025] The identification equipment 6 ~~can be of a type known per se~~ may include conventional identification equipment. Thus, for example, the party 1 can produce an impression ~~in a manner known per se~~ using conventional means. Alternatively, cameras, laser equipment, etc., can be used. The computer appliance 7 comprises, ~~in a manner known per se,~~ a computer screen 7a and an operating element 7b which can consist of a keyboard, voice communication unit, etc. [[.]] Depending on the identification, the relevant jaw/jaw bone, in this case upper jaw, of the patient 4 can be indicated. The upper jaw structure is symbolized by 7c. In addition, the first party can modify the computer model of the jaw bone structure on the screen and build up a dental crown structure applied on the jaw bone. Such a structure is indicated by 7d. For the sake of clarity, the upper jaw 7c and the complete structure 7d have

been shown as two simultaneous representations. Said representations can of course be indicated one at a time. In the representation 7d, the orientations for the implants and their directions are shown by 7e. The computer appliance can operate with conventional programs (CAD programs), ~~which are available on the market,~~ and file management systems. ~~The stereolithography machine can be of a type known per se and will therefore not be described in detail here.~~

[0026] The scanning equipment 6 ~~of certain embodiments provides~~ can provide the computer appliance with first information 12 which represents the scanned jaw bone structure. This is exported to the computer appliance. In turn, the computer appliance generates a CAD file which is represented by 13 in FIG. 1. The CAD file is received by the stereolithography machine which sets the conditions for a physical model transferred to the dental technician 9 for application of sleeves, inter alia. This transfer is represented by 14. The physical model is shown by 15. The dental technician uses the model 15 for production of a working model 16, and the transfer function between the units 9 and 10 is symbolized by 17. The production of the working model takes place in conjunction with an articulator function which is represented by 18. The bite index for the articulator function can be transferred from the patient 4, the computer appliance 7 and/or the identification equipment 6. Said transfers are represented by 19, 20 and 21. ~~At entry to the articulator function,~~ The bite index transfer to the articulator function has been symbolized by 22.

[0027] The real dental bridge 23 is produced in the equipment 11 by the party 3. From the equipment 9, the physical template 15 can be transferred to the surgeon or equivalent. This transfer is represented by 24. The party 1 can also have access to equipment symbolized by 1A. This equipment can ~~consist-include~~ of drilling equipment and insertion equipment for fitting the template and dental bridge on the patient 4. The finished dental bridge can be transferred to the first party, as has been represented by the transfer arrow 26. Formation of holes in the patient's jaw bone with the aid of the template and insertion of the finished dental bridge can take place in a manner known per se and will therefore not be described in detail here.

[0028] In accordance with FIG. 1, the fourth party 5 can provide a support function or production of one or more of said function steps. This is shown in the figure where the



automatic system comprises adaptation units 27, 28, 29 and 30. The equipment of the other parties can also be connected via adaptation units 31, 32, 33, 34, 35, 36, 37 and 38. The transfers can take place via general communication means 39, for example the telecommunications network, Internet, computer network, etc. The transfer functions are represented by two bi-directional arrows, ~~which indicates~~ indicating ~~that two-way communications exist.~~ The arrows are represented by 40.

[0029] In FIG. 2, an upper jaw of a patient is indicated by 41 and a lower jaw by 42. In the upper jaw, the party 1 has inserted implants 43 in which a dental bridge is to be secured. A set of teeth in the patient's lower jaw is indicated by 44 and, in accordance with ~~what has been explained above~~ embodiments described herein, the bite relationship between the dental bridge to be implanted and the teeth of the lower jaw ~~has been effected~~ can be implemented and/or determined with the aid of a bite index. Reference number 45 indicates a template in accordance with the above. The template comprises, ~~inter alia~~, recesses 46 for sleeves 47. The sleeves can be used as guide members for formation of holes 48 ~~in into~~ which the implants 43 ~~are to~~ can be screwed or recessed. Reference number 49 indicates the finished dental bridge structure to be anchored on the implants 43 in the upper jaw. The upper jaw is also shown diagrammatically from underneath by reference number 50 in order to indicate orientations for anchoring pins 51 which may extend substantially in a horizontal plane in the jaw structure. FIG. 3 shows a first embodiment of a sleeve 52 which is used for guiding a drill 53 for forming the implant hole 48. The sleeve has a stop edge 52a which can cooperate with the template 54 via a stop surface 54a on the latter. FIG. 3 also shows a second embodiment 55 of a sleeve 56 which is provided with slits 56a. The template 57 in this case has an internal recess 57a into which a snap-fit flange 56b on the sleeve can snap when the sleeve assumes its final position in the template 57. A click noise may sound upon snap-fitting of the flange 56b into the recess 57. ~~function can be provided.~~

[0030] FIG. 4 shows an implant 60 applied in a jaw bone and dentine 59. The implant can cooperate with an attachment part 61 over which a sleeve 62 in accordance with the above can be engaged. The components can be held together with a retaining screw 63. The sleeve 62 ~~is~~ may be mounted in the template or dental bridge part which is indicated by 64. The parts are shown in the disassembled state for the sake of clarity. The parts can be joined

together in the direction of the arrow 65. A through-hole in the template 64 is shown by 64a. Cement which is used for securing the sleeve to the template is shown symbolically by 52b.

[0031] A structural configuration of a physical template is indicated by 66 of FIG. 5 and FIG. 6. In the present embodiment, implants 67 are ~~serewed-seeurely~~ secured to the template in an assembled configuration, ~~compare with FIG. 4.~~ The ~~pins for anchoring~~ anchoring pins are shown by 68. FIG. 6 shows the template according to FIG. 5 from underneath. The anchoring pins 68 are designed with manual actuating members ~~by means of which the pins~~ configured to allow for screwing of the pins ~~can be serewed~~ through the jaw bone in question. ~~The figure shows~~ As shown, ~~that the anchoring pins~~ may extend between the implants 67.

[0032] FIG. 7 shows, from the side and in perspective, the template according to FIGS. 5 and 6 applied to a jaw bone 69.

[0033] Although this disclosure has been described in terms of example embodiments and applications, other embodiments and applications apparent to those of ordinary skill in the art, including embodiments and applications that do not provide all of the benefits described herein, are also within the scope of this disclosure. The scope of the inventions is defined only by the claims, which are intended to be construed without reference to any definitions that may be explicitly or implicitly included in any of the incorporated-by-reference materials. The invention is not limited to the embodiment described above by way of example, and instead it can be modified within the scope of the attached patent claims and the inventive concept